



ردیف قلم	شماره قطعه	مشخصات کالا	واحد	مقدار	بهاء واحد به عدد ((ریال))	بهاء واحد به حروف ((ریال))	قیمت کالا ((ریال))
		SQUARE DRIVE :1-1/2", IMPACT PER MINUTE:700 TWIN HAMMER MECHANISM, MAX WEIGHT:16KG TORQUE FORWARD RANGE:2169-5268 Nm TORQUE REVERSE RANGE:2170-5630 Nm AIR INLET SIZE: 1/2" NPT, HANDEL :GRIP IT RPM:2750, MAX TORQUE: 6780Nm	ST	1			
		PNEUMATIC IMPACT WRENCH					
		EXTENTION: OUTPUT SIZE:1-1/2" WITH 5"	NO	1			
		EXTENTION: OUTPUT SIZE:1-1/2" WITH 10"	NO	1			
		SPRING BALANCERS WITH CAPACITY (SWL)	NO	1			
		UNIVERSAL JOINT FOR 1-1/2" DRIVER	NO	1			
		IMPERIAL HEXAGON AF SIZE HEAVY DUTY SOCKET					
		SOCKET SIZE ARE REQUIRED (AF) : 1- 1/4"	NO	1			
		SOCKET SIZE ARE REQUIRED (AF) : 1- 5/8"	NO	1			
		SOCKET SIZE ARE REQUIRED (AF) :1- 7/8"	NO	1			
		SOCKET SIZE ARE REQUIRED (AF) : 1-13/16"	NO	1			
		SOCKET SIZE ARE REQUIRED (AF) : 2"	NO	1			
		SOCKET SIZE ARE REQUIRED (AF) : 2-3/16"	NO	1			
		SOCKET SIZE ARE REQUIRED (AF) : 2-3/8"	NO	1			
		SOCKET SIZE ARE REQUIRED (AF) : 2-3/4"	NO	1			
		SOCKET SIZE ARE REQUIRED (AF) : 2-15/16"	NO	1			
		SOCKET SIZE ARE REQUIRED (AF) : 2-9/16"	NO	1			
		SOCKET SIZE ARE REQUIRED (AF) : 3-1/8"	NO	1			
SND_0000074							



					اصلاحیه حذف اقلام 03 و 04 SPECIAL TOOLS FOR MECHANIC WORK SHOPS IN NAR & KANGAN & GAS STATION NAR AREA		
			1	ST	HYDRAULIC TORQUE WRENCH CASSETTE TYPE WORKING PRESSURE : 10000 PSI (700 BAR) TORQUE RANGE: 6466- 43000 N.M BOLT RANGE: (65 - 155 MM)		1
			1	NO	ELECTRIC POWERED TORQUE WRENCH PUMP ,220 V , PH1		2
			1	NO	RATCHET LINK FOR NUT 80 MM		5
			1	NO	RATCHET LINK FOR NUT 96 MM		6
			1	NO	RATCHET LINK FOR NUT 135 MM		7
			1	NO	RATCHET LINK FOR NUT 155 MM		8
SND_0100347							



					جهت تعمیرات شیر آلات خطوط 36-42 و 48 اینچ و تعمیرات اساسی 1402 دستگاه می بایست دارای 1 سال گارانتی و 5 سال خدمات پس از فروش باشد فلنج باز کن هیدرولیک HYDRAULIC TOOLS MAXIMUM SPREAD FORCE : 25 TON MAXIMUM OPERATION PRESSURE : 700 BAR TIP CLEARANCE : 6 MM , MAXIMUM SPREAD : 81 MM		
			4	NO	HYDRAULIC WEDGE SPREADER :		1
			2	NO	HAND PUMP 700 BAR HP550DMINEX		2
			2	ST	SEALED WITH GAUGES		3
			4	NO	SET OF STEPPED BLOCK		4
			2	NO	SPLIT- FLOW MANIFOLD 2 WAY		5
			2	NO	700 BAR HYDRAULIC HOSES 2M WITH 90° ELBOW		6
			2	NO	700 BAR HYDRAULIC HOSES 3M WITH 90° ELBOW		7
			2	NO	700 BAR HYDRAULIC HOSES 6M WITH 90° ELBOW		8
			4	NO	SET OF SAFETY BLOCK		9
			4	NO	HYDRAULIC WEDGE SPREADER		10
					SND_0100348		
					جهت تعمیرات شیر آلات خطوط 36-42 و 48 اینچ و تعمیرات اساسی 1402 ELECTRIC IMPACT WRENCH DRIVE SIZE:1-1/2 , MAX. TORQUE:16000 Nm SPEED:2 RPM, BLUETHOOH, WITH CONTROLLER WEATHERPROOF ASSEMBLY, WEIGHT: 20kg DRIVE: 1-1/2" SMART SOCKET MEASURES AND DISPLAYS PEAK TORQUE RECHARGABLE BATTERY		
			1	ST			1
			1	NO	65 mm SMART SOCKET DRIVE 1-1/2		2
			1	NO	70 mm SMART SOCKET DRIVE 1-1/2		3



			1	NO	80 mm SMART SOCKET DRIVE 1-1/2		4
			1	NO	90 mm SMART SOCKET DRIVE 1-1/2		5
			1	NO	100 mm SMART SOCKET DRIVE 1-1/2 خریداری شود RAD از برند E-RAD BLU 15K ترجیحاً مدل جهت بستن یکنواخت درب کلیه مخازن نیاز به ترک مشخص و یکنواخت میباشد که از سوکت هوشمند در این دستگاه استفاده شده است.		6
					SNL_0100349		
			1	ST	جهت تعمیرات شیر آلات خطوط 42-36 و 48 اینچ و تعمیرات اساسی 1402 PNEUMATIC IMPACT WRENCH TYPE OF HANDLE : LEVER THROTTLE MAX TORQUE: 108500Nm WEIGHT: 276kg DRIVE: 3-1/2" SQUARE		1
			2	NO	SOCET DRIVE 3-1/2" 155MM		2
			2	NO	SOCET DRIVE 3-1/2" 135MM Ingersoll Rand از شرکت A1 ترجیحاً مدل 599		3
					SNL_0100350		
			1	ST	جهت تعمیرات شیر آلات خطوط 42-36 و 48 اینچ و تعمیرات اساسی 1402 HYDRAULIC TORQUE WRENCH TORQUE RANGE: 50000 N.M WITH CHANGEABLE CASSETTE RATCHET HEAD BOLT SIZE: 96-155 mm LOCATION: PHASE 2 SATES HYDRAULIC TORQUE WRENCH HI-FORCE پیشنهاد می گردد از برند خریداری شود TWH430 N مدل		1
					ZRD_0200835		



			1	ST	<p>Super duty impact wrench Specifications: Configuration:T-handle Actuation:lever Drive size (in)=2 1/2 ,Drive type =square thru hole Max torque:50000 , Free speed:355RPM Blows per minute (BPM):550 sound level dB(A):110/121 Air inlet (in):1 , min hose size (in):1 Recommended model: Ingersolrand 588A1 از زمان تحویل دارای 2 سال گارانتی باشد. لازم به ذکر است قبل از ارسال کالا، حضور کارشناس این امور جهت تست الزامی می باشد</p>		1
					SAD_0200255		
			2	ST	<p>اقلام مورد نیاز مکانیک دالان PNEUMATIC IMPACT WRENCH TYPE OF HANDLE : LEVER THROTTLE MAX TORQUE:1495Nm, WEIGHT: 6kg AIR PRESSURE= 7BAR DRIVE: 3/4" SQUARE</p>		1
			2	ST	<p>PNEUMATIC IMPACT WRENCH TYPE OF HANDLE : LEVER THROTTLE MAX TORQUE: 2850Nm, WEIGHT: 10.5kg AIR PRESSURE= 7BAR DRIVE: 1" SQUARE</p>		2
			2	ST	<p>PNEUMATIC IMPACT WRENCH TYPE OF HANDLE: LEVER THROTTLE MAX TORQUE: 13560Nm, WEIGHT: 39.9kg AIR PRESSURE= 7BAR DRIVE: 1-1/2" SQUARE</p>		3
			2	ST	<p>PNEUMATIC IMPACT WRENCH TYPE OF HANDLE : LEVER THROTTLE MAX TORQUE:5288Nm, WEIGHT: 15.7kg AIR PRESSURE= 7BAR DRIVE: 1-1/2" SQUARE</p>		4



			2	ST	TYPE OF HANDLE : LEVER THROTTLE SQUIRE DRIVE, SIZE: 2 -1/2", IMPACTS PER MIN : 550 TORQUE RANGE : 12000-25000 ft-lb AIR PRESSURE= 7BAR DRIVE: 2-1/2" SQUARE		5
		به عدد	قیمت کل کالا	توضیحات			
		به حروف	((ریال))				
		به عدد	هزینه بسته بندی				
		به حروف	((ریال))				
		به عدد	هزینه حمل				
		به حروف	((ریال))				
		به عدد	جمع کل	شیراز خیابان زند جنب کوچه پروانه - ساختمان شرکت ملی نفت ایران - شرکت بهره برداری نفت و گاز زاگرس جنوبی (تدارکات کالا) - واحد 506 - روح الله پسندیده تلفن (07132138436) فاکس (07132314447) ایمیل ()			
		به حروف	((ریال))				
نام و امضاء و مهر فروشنده:							