



ردیف قلم	شماره قطعه	مشخصات کالا	واحد	مقدار	بهاء واحد به عدد	بهاء واحد به حروف	قیمت کالا
		اقلام مورد نیاز واحد خط لوله منطقه سروستان و سعادت آباد  LINE PIPE,CARBON ,STEEL,BLACK,SMLS ,PSL-2 ,BEVELLED ENDS, FOR SOUR SERVICE API 5L(45 th Edition), GR X52 NS,ISO3183 LENGTH:12 m (Approximate Length) ACC TO REQUIREMENTS OF ANNEX H NDT ACC TO ANNEX K, .INSPECTION CERTIFICATE ACC (2004)TO EN10204-3.1	MT	240			
		line pipe size 6" w.t=12.70 mm					1
		line pipe size 6" w.t=14.27 mm					2
slp_4020910045							
		تمامی مدارک مورد نیاز بازرسی فنی باید از سوی نامین کننده ارائه و مورد تایید بازرسی فنی زاگرس جنوبی قرارگیرد					
		PIPE, API 5L ( EDITION 46) Carbon steel, PSL2, SMLS (SEAMLESS) BEVEL ENDS TEMPORARY , COATING , DIMENTION ACC. TO ANSI B36.10M , SUITABLE FOR SOUR SRVICE ACC. TO API 5L ANNEX H AND IN COMPLIANCE WITH NACE MR-0175 ISO 15156 12MT APPROXIMATE LENGTH SIZE WT.IN OD.MM SCHED NO	MT	600			
		NOM 12 IN 0.625 IN GR X52 NS					1
		NPS: 8 INCH WT : 0.5" SCH 80 GR : X52 NS					2
		Line Pipe, NPS: 8 in; Gr: X52 NS ,Wt: 0.438 in					3
		Line Pipe,NPS: 10 in; Gr: X65 QS , Wt: 0.438 in					4



					LINE PIPE, API 5L EDITION 46 - Carbon steel PSL2, SAWL ,WITH ONE SEAM, SUBMERGED ARC WELD BEVEL ENDS, 12 MT. APPROXIMATE LENGTH TEMPORARY COATING Dimention ACC TO ANSI B36.10M , SUITABLE FOR SOUR SRVICE ACC.TO API 5L ANNEX H , AND IN COMPLIANCE WITH NACE MR-0175 ISO 15156			
			1500	MT	NOM 24 IN WT: 0.969 IN SCH 60 GR X60 QS		5	
			360	MT	PIPE, NOM :24 IN SCH:100 GR X52 NS		6	
			480	MT	PIPE, NOM : 30 IN WT: 38mm GR X60 QS		7	
			360	MT	PIPE, NOM : 24 IN SCH:140 GR X60 QS		8	
			204	MT	SIZE: 20 INCH O.D. WT : 0.75" GR : X60 QS		9	
			360	MT	SIZE : 30 INCH O.D. WT : 0.875" GR : X60 QS		10	
			120	MT	SIZE : 48 INCH O.D. WT : 2" GR : X60 QS		11	
			480	MT	Line Pipe, NPS: 24 in; Grade: X52 NS; Wt: 1 in WITH ONE SEAM, SUBMERGED ARC WELD		12	
							slp_4020910046	



					<p>تمامی مدارک مورد نیاز بازرسی فنی باید از سوی نامین کننده ارائه و مورد تایید بازرسی فنی زاگرس جنوبی قرارگیرد</p> <p>PIPE, API 5L ISO 3183 (LAST EDITION)/ , CARBON STEEL, GRADE X52N(NORMALIZED) -S, PSL2, SMLS (SEAMLESS), PLAIN ENDS ,TEMPORARY , COATING , DIMENTION ACC. TO ANSI B36.10M , SUITABLE FOR SOUR SRVICE ACC. TO API 5L ISO3183 ANNEX H AND IN COMPLIANCE WITH NACE MR-0175 ISO 15156 ,HIC &amp; SSC TESTS ARE REQUIRED , 12MT APPROXIMATE LENGTH INSPECTION, CERTIFICATE ACC. TO EN 10204-3.2 -2004 NDT ACC TO ANNEX E&amp; K OF API 5L/ISO 3183 SIZE WT.IN OD. MM SCHED NO</p>		
			120	MT	NOM 6 IN	XXS	1
			120	MT	NOM 8 IN	0.625 IN	2
			36	MT	NOM 10 IN	1.25 IN	3
			180	MT	NOM 12 IN	0.750 IN	4
			60	MT	NOM 12 IN	1.312 IN	5
			24	MT	<p>PIPE, API 5L ISO 3183 LAST. EDITION / , GR X52N - S PSL2, SAWL, PLAIN ENDS, 12 MT. APPROXIMATE LENGTH TEMPORARY COATING, SUITABLE FOR SOUR SRVICE ACC. TO API 5L/ISO 3183 ANNEX H , HIC , SSC TESTS ARE REQUIRED NACE MR-0175 ISO 15156 INSPECTION CERTIFICATED ACC. TO EN 10204-3.1 (2004) NDT ACC. TO ANNEX E &amp; K OF API 5L/ISO 3183</p>		6
			60	MT	<p>PIPE, API 5L ISO 3183 LAST. EDITION / GR X60 Q -S PSL2, SAWL, PLAIN ENDS, 12 MT. APPROXIMATE LENGTH TEMPORARY COATING, SUITABLE FOR SOUR SRVICE ACC. TO API 5L/ISO 3183 ANNEX H , HIC , SSC TESTS ARE REQUIRED NACE MR-0175 ISO 15156 INSPECTION CERTIFICATED ACC. TO EN 10204-3.1 (2004) NDT ACC. TO ANNEX E &amp; K OF API 5L/ISO 3183</p>		7



			36	MT	PIPE, API 5L ISO 3183 LAST. EDITION / GR X65 Q -S PSL2, SAWL, PLAIN ENDS, 12 MT. APPROXIMATE LENGTH TEMPORARY COATING, SUITABLE FOR SOUR SRVICE ACC. TO API 5L/ISO 3183 ANNEX H , AND IN COMPLIANCE WITH NACE MR-0175 ISO 15156 , INSPECTION CERTIFICATED ACC. TO EN 10204-3.1 (2004) , TEMPORARY COATING COLOUR IDENTIFICATION , NDT ACC. TO ANNEX E & K OF API 5L/ISO 3183 , HIC & SSC TESTS ARE REQUIRED  NOM 16 IN WT: 0.562 IN		8
			36	MT	NOM 24 IN WT: 0.750 IN		9
			24	MT	PIPE, API 5L ISO 3183 LAST. EDITION / GR BN (NORMALZED) -S PSL2, PLAIN ENDS, 12 MT. APPROXIMATE LENGTH SUITABLE FOR SOUR SRVICE ACC. TO API 5L/ISO 3183 ANNEX H , HIC , SSC TESTS ARE REQUIRED AND COMPLIANCE WITH NACE MR-0175 ISO 15156 INSPECTION CERTIFICATED ACC. TO EN 10204-3.1 (2004) TEMPORARY COATING NDT ACC. TO ANNEX E & K OF API 5L/ISO 3183  NOM 24 IN WT: 0.375 IN		10
			24	MT	NOM 28 IN WT: 0.375 IN		11
			60	MT	PIPE, API 5L ISO 3183 LAST. EDITION / GR BN (NORMALZED) -S PSL2, SMLS , PLAIN ENDS, 12 MT. APPROXIMATE LENGTH SUITABLE FOR SOUR SRVICE ACC. TO API 5L/ISO 3183 ANNEX H , HIC , SSC TESTS ARE REQUIRED AND IN COMPLIANCE WITH NACE MR-0175 ISO 15156 INSPECTION CERTIFICATED ACC. TO EN 10204-3.1 (2004) TEMPORARY COATING NDT ACC. TO ANNEX E & K OF API 5L/ISO 3183  NOM 8 IN WT: 0.277 IN		12
			60	MT	NOM 6 IN SCH:STD		13



			84	MT	PIPE, CARBON STEEL, BLACK , SEAMLESS, ASTM A333 GRADE 6 BEVELLED ENDS, MAT.: ELECTRIC FURNACE OR BASIC OXYGEN TO ASTM A333 , 12 MT. APPROXIMATE LENGTH , 12 MT. APPROXIMATE LENGTH , SUITABLE FOR SOUR SRVICE ACC.TO - NACE MR-0175 ISO 15156 INSPECTION CERTIFICATED ACC. TO EN 10204-3.1 (2004)			14
			60	MT	NOM 6 IN SCH:40			15
			180	MT	NOM 12 IN SCH:30			16
			96	MT	PIPE, API 5L ISO 3183 LAST. EDITION /ELECTRICAL RESISTANCE VELDING (ERW) , GR X52NS ,SMLS (SEAMLESS) PSL2, BEVELED END, 12 MT. APPROXIMATE LENGTH TEMPORARY COATING, SUITABLE FOR SOUR SRVICE SUITABLE FOR SOUR SRVICE ACC. TO API 5L ANNEX H INSPECTION CERTIFICATED ACC. TO EN 10204-3.2 (2004) NDT ACC. TO ANNEX E & K OF API 5L/ISO 3183			17
					slp_4020910047			
			48	MT	PIPE, API 5L ISO 3183 (LAST EDITION)/ , CARBON STEEL, GRADE X52N-S, PSL2, SMLS (SEAMLESS), PLAIN ENDS , TEMPORARY , COATING , DIMENTION ACC. TO ANSI B36.10M , SUITABLE FOR SOUR SRVICE ACC. TO API 5L ISO3183 ANNEX H AND IN COMPLIANCE WITH NACE MR-0175 ISO 15156 ,HIC & SSC TESTS ARE REQUIRED , APPROXIMATE LENGTH , INSPECTION, CERTIFICATE ACC. TO EN 10204-3.2 -2004 NDT ACC TO ANNEX K OF API 5L/ISO 3183			1
			48	MT	SIZE WT.IN OD. MM SCHED NO			2
			36	MT	NOM 3 IN 160			3
			36	MT	NOM 4 IN 80			4



					PIPE, API 5L ISO 3183(LAST EDITION ), CARBON STEEL, GRADE BN-S, SMLS (SEAMLESS), PSL2, PLAIN ENDS, APPROXIMATE LENGTH, SUITABLE FOR SOUR SRVICE ACC. TO API 5L ISO 3183 ANNEX H AND IN COMPLIANCE WITH NACE MR-01-075 ISO 15156, HIC & SSC TESTS ARE REQUIRED, DIMENTION ACC. TO ANSI B36.10M, INSPECTION CERTIFICATED ACC. TO EN 10204-3.2 (2004) NDT ACC. TO ANNEX K OF API 5L/ISO 3183		
			72	MT	NOM 1/2 IN	XS	5
			72	MT	NOM 1/2 IN	160	6
			60	MT	NOM 1/2 IN	XXS	7
			120	MT	NOM 3/4 IN	XS	8
			72	MT	NOM 3/4 IN	160	9
			72	MT	NOM 3/4 IN	XXS	10
			120	MT	NOM 1 IN	XS	11
			72	MT	NOM 1 IN	160	12
			72	MT	NOM 1 IN	XXS	13
			72	MT	NOM 1- 1/4 IN	XXS	14
			60	MT	NOM 1-1/2 IN	XS	15
			60	MT	NOM 1-1/2 IN	XXS	16
			72	MT	NOM 2 IN	XXS	17
			180	MT	NOM 2 IN	XS	18
			72	MT	NOM 2 IN	160	19
			36	MT	NOM 2-1/2 IN	160	20
			72	MT	NOM 3 IN	STD	21
			60	MT	NOM 3 IN	XS	22
			60	MT	NOM 3 IN	160	23
			60	MT	NOM 3 IN	XXS	24
			72	MT	NOM 4 IN	STD	25



			36	MT	NOM 4 IN	XS		26
			36	MT	NOM 4 IN	120		27
			36	MT	NOM 4 IN	160		28
			36	MT	NOM 4 IN	XXS		29
					PIPE, CARBON STEEL, BLACK, SEAMLESS, ASTM A333, GRADE 6, BEVELLED ENDS, MAT: ELECTRIC FURNACE OR BASIC OXYGEN TO ASTM A333, RANDOM LENGTH, SUITABLE FOR SOUR SERVICE ACC. TO NACE-MR-01-075/ ISO15156, INSPECTION CERTIFICATE ACC. TO EN 10204-3.1 (2004)			
			36	MT	NOM 3/4 IN	XS		30
			36	MT	NOM 1 IN	XS		31
			36	MT	NOM 1-1/2 IN	XS		32
			36	MT	NOM 2 IN	XS		33
			36	MT	NOM 3 IN	40		34
			36	MT	NOM 4 IN	40		35
					slp_4020910043			
					لوله های مورد نیاز سه ساله اداره تعمیرات پارسین (سایز کوچکتر از 3 اینچ) CERTIFICATE ACC TO EN10204.3.1, Length: Random 12(m)			
			48	MT	NPS 1/2, SMLS,ASTM A106 Gr.B, SCH80, BE, ASME B36.10			1
			48	MT	NPS 1/2, SMLS,ASTM A106 Gr.B, SCH160, BE, ASME B36.10			2
			48	MT	NPS 3/4, SMLS,ASTM A106 Gr.B, SCH80, BE, ASME B36.10			3
			48	MT	NPS 3/4, SMLS,ASTM A106 Gr.B, SCH160, BE, ASME B36.10			4
			48	MT	NPS 1, SMLS,ASTM A106 Gr.B, SCH80, BE, ASME B36.10			5
			48	MT	NPS 1, SMLS,ASTM A106 Gr.B, SCH160, BE, ASME B36.10			6
			48	MT	NPS 2, SMLS, API 5L Gr.BN ,SCH80,BE,ASME B36.10 ,PSL2			7
			72	MT	NPS 2, SMLS, API 5L Gr.BN ,SCH40,BE, ASME B36.10 ,PSL2			8
					slp_4020910044			



					لوله های مورد نیاز سه ساله اداره تعمیرات پارسین (سایز های 3 الي 20 اینچ) Acc to API 5L/ISO 3183 Edition 44th SMLS, BEVEL END, NDE Requirement Acc to Annex E Inspection Certificate acc to EN 10204 (2004 type 3.1), Length: Approximate (12m)			
			24	MT	NPS 3, SMLS, API 5L Gr. BN, SCH80, BE, ASMEB36.10, PSL2		1	
			48	MT	NPS 4, SMLS, API 5L Gr. BN, SCH 40, BE, ASME B36.10, PSL2		2	
			48	MT	NPS 4, SMLS, API 5L Gr. BN, SCH 80, BE, ASME B36.10, PSL2		3	
			36	MT	NPS 4, SMLS, API 5L Gr. BN, SCH 160, BE, ASMEB36.10, PSL2		4	
			36	MT	NPS 4, SMLS, API 5L Gr. X52N, SCH 80, BE, ASMEB36.10, PSL2		5	
			60	MT	NPS 6, SMLS, API 5L Gr. X52N, W.TH: 0.625",BE, ASME B36.10, PSL2		6	
			48	MT	NPS 6, SMLS, API 5L Gr. X52N, W.TH:0.719",BE, ASME B36.10, PSL2		7	
			24	MT	NPS 8, SMLS, API 5L Gr. X52N, W.TH:0.5", BE, ASME B36.10, PSL2		8	
			84	MT	NPS 8, SMLS, API 5L Gr. X52N, W.TH:0.719",BE, ASME B36.10, PSL2		9	
			60	MT	NPS 10, SMLS,API 5L Gr. X52N, W.TH:0.625",BE, ASME B36.10, PSL2		10	
			60	MT	NPS 10, SMLS, API 5L Gr. X52N,BE, ASME B36.10, PSL2 SCH 40 (W.TH:0.365")		11	
			24	MT	CERTIFICATE ACC TO EN10204.3.1, Length: approximate 12(m) - ",BE, ASME B36.10, PSL2 NPS 20, SMLS, API 5L Gr. X52N, W.TH:0.938"		12	
		توضیحات						
		قیمت کل کالا			به عدد			
		هزینه بسته بندی			به عدد			
		هزینه حمل			به عدد			
		جمع کل			به عدد			
		نام و امضاء و مهر فروشنده:						
<p>شیراز خیابان زند جنب کوچه پروانه - ساختمان شرکت ملی نفت ایران - شرکت بهره برداری نفت و گاز زاگرس جنوبی (تدارکات کالا) - واحد 506 - روح الله پسندیده تلفن (07132138436) فاکس (07132314447) ایمیل ()</p>								